

STORM DAMPSPÆRREFOLIE 30

Declaration of Performance no. 01/2014 according to EU 305/2011

1. Product type	STORM Dampspærrefolie 30 Green tinted
2. Identification of the product	Lot no. see packaging
3. Intended use/uses of the product	Flexible sheets for waterproofing – Plastic and rubber vapour control layers EN 13984
4. Name and contact address of manufacturer	Eric Storm A/S Energivej 27, 5260 Odense S
5. Authorised representative	N/A
6. AVCP: System of assessment and verification of constancy of performance of the construction product	System 4
7. Notified body (hEN)	N/A
8. Notified body (ETA)	N/A

9. Declaration of Performance. Harmonised technical specification EN 13984:2005

			Thickness 0.150mm	Thickness 0.200mm
ESSENTIAL CHARACTERISTICS	METHOD	UNIT	PERFORMANCE	PERFORMANCE
Reaction to fire	EN 13501-1	Class	F	F
Resistance to water penetration	EN 1928	2 kPa	Pass	Pass
Water vapour transmission	EN 1931	0/+20m	70	87
Tensile strength longitudinal	EN 12311-2	N/5cm-0+20%	110	150
Tensile strength transverse	EN 12311-2	N/5cm-0+20%	90	130
Elongation longitudinal	EN 12311-2	%	>250	>250
Elongation transverse	EN 12311-2	%	>400	>400
Tear resistance longitudinal	EN 12310-1	N-0/+20%	45	61
Tear resistance transverse	EN 12310-1	N-0/+20%	47	62
Durability – aging*	EN 1296	Years	30	30
Resistance to Alkali	EN 13984		Pass	Pass
Shear resistance of joints	EN 12317-2		NPD	NPD
Resistance to impact	EN 12691		NPD	NPD
Length	EN 1848-2	m	-0/+3%	-0/+3%
Width	EN 1848-2	m	-0/+50mm	-0/+50mm
Straightness	EN 1848-2		75mm/10m	75mm/10m
Mass per unit	EN 1849-2	g/m ² ±7%	0,138	0,184

NPD: No performance determined

STORM DAMPSPÆRREFOLIE 30

Declaration of Performance no. 01/2014 according to EU 305/2011

*The performance of the product identified in points 1-2 is in conformity with declared performance of point 9 if handled with professional competence - avoiding sunshine destruction action (UV rays), other severe and aggressive factors – meaning for construction purpose in buildings.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and behalf of the manufacturer by:

Odense the 30.6.2014

Martin S. Henriksen, Salgschef

