

PRODUCT DESCRIPTION

Item number:	M3: 325421 / DB: 2491459
Product name:	Solid Classic Washed Oak. 5,2 x 220 x 1510 mm.



Product description	
Appearance	Wood surface texture, the decor contains 6 different planks.
Pattern of surface	1 strip, wide plank
Material	100% virgin PVC, calcium carbonate, plasticizer, stabilizer, IXPE
Surface	Overall embossing
Finishing	UV coating, gloss 6-8
Bevel	Four-sided micro bevel
Density pr. m ²	8.58 kg/m ²
Hardness / class	34
Floor heating installation	Yes, max 27° on surface

Dimensions	
Lenght	1510 mm
Width	220 mm
Thickness	5.2 mm
Top layer	0.55

☒ Cleaning and maintenance instructions:

☐ Can be used for eco-label construction

☐ FDV-documentation

☒ EPD

☒ IACG Gold



PRODUCT DESCRIPTION

Technical specification			
Dimension	5.2 x 220 x 1510 mm	Delamination	Not allowed
Top layer	0.55	Torn grain	Not allowed
Middle layer	4.2 mm	Colour on bevel and surface	Homogeneous expression
Bottom layer	1.0	Pressure Marks	Not allowed
Locking method end	I4F - DL100	Product marking	CE
Locking method longside	I4F - DL100	Noice reduction with IXPE	18 db
Fire class	B _{fl} - s1	Boards pr. box / m ²	6 boards = 1.993 m ²
Formaldehyde content	E1	Weight pr. box	17.56 kg.
Thermal conductivity	0.102		

Data		
Maximum intallation area	125 m2 for private homes, up to 1000m2 in one square (33x33m)	
Ortho - Phthalates	Norms: US EPA 3350c:2007	Result: Phthalate-free
SVOC	Norms: EN ISO 14041:2014	Result: ND
Light fastness	Norms: EN ISO 105 B02	Result: ≥Grade 6
Abrasion resistance	Norms: EN 13329, EN 16094	Result: ≥4,000 cycles MSR-A2 / MSR-B1
Slip resistance	Norms: DIN 51130	Result: R10
Residual indentation	Norms: ISO 24343-1:2007	Result: ≤0.15 mm
Resistance to staining	Norms: EN ISO 26987:2012	Result: 0 (Not affected / unchanged)